

Polyurethane Based, Excellent UV Resistance, Porous Substrates, Wood Floors

EAN-Code
6151154910968



Options: 4kg, 20kg

Description

Primer® D-1K is a one component low viscosity polyurethane fluid that cures with the humidity in the atmosphere. It is especially designed to enhance the adhesion of polyurethane high solids products on porous substrates.

Has an increased curing speed (same day primer) which allows it to be used more successfully in cold weather and when rain is not very predictable.

Packaging Types

4kg

20kg

Pallet Description

4kg	150pcs X 4kg	Total 600kg
20kg	30pcs X 20kg	Total 600kg

Technical Specifications

PROPERTY	UNITS	METHOD	SPECIFICATION
Viscosity (Brookfield)	cP	at 20 °C	75-115
Specific weight	cP	at 25 °C	0.95-1.05
Tack free time, at 77deg F (25 °C) & 55% RH	hours	-	3-5
Flash Point	°C	Closed cup	28

Features / Benefits

- One component
- Non Staining
- Easy application

Application Areas

- Priming of porous substrates
- Porous concrete
- Wood floors
- Concrete, sealing
- Ceramic tiles

Technical Data

Potlife : ± 25 minutes (20 °C)

Drying Time : 1 hours (25 °C)

Consumption

- 150-250 gr/m²

Application Procedure

Clean the surface using a high pressure washer if possible.

Remove oil, grease and wax contaminants. cement laitance, loose particles, mould release agents, cured membranes must also be removed. The application surface must be dry.

Apply with brush or roller depending on the surface to be primed at a consumption of 150-250 gr/m². Ensure primer has cured before applying stone carpet.